

[54] INTRAVASCULAR DEVICE

[75] Inventor: Phillip D. Purdy, Dallas, Tex.

[73] Assignee: Board of Regents, The University of Texas System, Austin, Tex.

[*] Notice: This patent is subject to a terminal disclaimer.

[21] Appl. No.: 08/938,081

[22] Filed: Sep. 26, 1997

Related U.S. Application Data

[62] Division of application No. 08/662,845, Jun. 12, 1996, Pat. No. 5,693,067, which is a division of application No. 08/164,398, Dec. 9, 1993, Pat. No. 5,527,338, which is a continuation-in-part of application No. 07/939,296, Sep. 2, 1992, Pat. No. 5,443,478.

[51] Int. Cl.⁶ A61M 29/00

[52] U.S. Cl. 606/200

[58] Field of Search 606/1, 198, 200;
128/898, 899; 623/1, 12

[56] References Cited

U.S. PATENT DOCUMENTS

3,540,431 11/1970 Mobim-Uddim .
3,794,041 2/1974 Frei et al. .
3,868,956 3/1975 Alfidi et al. .
4,365,632 12/1982 Kortum .
4,425,908 1/1984 Simon .
4,447,227 5/1984 Kotsanis .
4,494,531 1/1985 Gianturco .
4,512,338 4/1985 Balko et al. .
4,619,246 10/1986 Mølgaard-Nielsen et al. .
4,638,803 1/1987 Rand .
4,957,501 9/1990 Lahille et al. 606/200

4,994,069 2/1991 Ritchart et al. .
4,997,435 3/1991 Demeter .
5,053,008 10/1991 Bajaj .
5,071,407 12/1991 Termin et al. .
5,104,404 4/1992 Wolff .
5,108,407 4/1992 Geramia et al. .
5,108,419 4/1992 Reger et al. .
5,217,484 6/1993 Marks 606/200
5,256,146 10/1993 Ensminger et al. .
5,263,964 11/1993 Purdy 606/200
5,443,478 8/1995 Purdy .
5,527,338 6/1996 Purdy .
5,693,067 12/1997 Purdy .

Primary Examiner—Michael Buiz

Assistant Examiner—William W. Lewis

Attorney, Agent, or Firm—Arnold White & Durkee

[57] ABSTRACT

A multi-element occlusion device (10, 20, 30, 40) provides an improvement over existing systems by increasing the occupation of a vascular lumen. The device (10, 20, 30) comprises an anchoring element (12, 22, 32), a lead element (14, 24, 34) and at least one fiber (16, 26, 36) attaching said elements. The elements and fibers produce a cumulative occlusive effect greater than the sum of the individual elements. When placed in the blood stream, the anchoring element (12, 22, 32) lodges against the vessel wall and the lead element (14, 24, 34) is carried to a position distal thereto. In another embodiment, an "umbrella" of support members extend from the lead element. A fabric web extends between these support members. The umbrella intravascular device expands upon its exit from the catheter. The fabric web produces complete occlusion of the vessel without the need for thrombosis to form between the elements. With the use of multi-element deployment, the device decreases the risk of continued canalization and recanalization.

21 Claims, 5 Drawing Sheets